

INFORMATION REPORT

CD NO.

FD  
683

COUNTRY Germany (Russian Zone)

DATE DISTR 19 AUG 50

25X1 SUBJECT Production of Reactors for the  
Oxidation of Paraffin; Production  
of Very Pure Aluminum

NO. OF PAGES 1

NO. OF ENCLS.  
(LISTED BELOW)

SUPPLEMENT TO 25X1A  
REPORT NO.

25X1X

25X1  
ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED EXCEPT WHERE SHOWN OTHERWISE. IT IS THE POLICY OF THE UNITED STATES GOVERNMENT TO MAKE SUCH INFORMATION AVAILABLE TO THE PUBLIC AS SOON AS IT IS DETERMINED THAT IT IS NOT IN THE INTEREST OF NATIONAL DEFENSE TO KEEP IT SECRET. IT IS THE POLICY OF THE UNITED STATES GOVERNMENT TO MAKE SUCH INFORMATION AVAILABLE TO THE PUBLIC AS SOON AS IT IS DETERMINED THAT IT IS NOT IN THE INTEREST OF NATIONAL DEFENSE TO KEEP IT SECRET. IT IS THE POLICY OF THE UNITED STATES GOVERNMENT TO MAKE SUCH INFORMATION AVAILABLE TO THE PUBLIC AS SOON AS IT IS DETERMINED THAT IT IS NOT IN THE INTEREST OF NATIONAL DEFENSE TO KEEP IT SECRET.

THIS IS UNEVALUATED INFORMATION

1. The Karl Fischer Apparate-und Rohrleitungsbau, at Reinsdorf/Wittenberg, produces reactors for the oxidation of paraffins for two East German plants and one Polish plant. An official of the Deutsches Hydrierwerk Rodleben is reportedly of the opinion that since the desired fatty acid capacity of these plants far exceeds that required for butter substitutes and soaps, this material is for munitions.
2. At the present time (June 1950), the following reactors have been furnished or are planned by the Fischer plant for the following hydrogenation plants:

Rodleben bei Dessau	8 reactors with 30 cubic meters' capacity delivered
	8 " " 40 " " " planned
Lützkendorf	16 " " 50 " " " "
Heydebreck (Poland)	12 " " 50 " " " "
3. These reactors are constructed of sheet aluminum, but the tops must be of acid-resistant material. Acid-proof steel is desired for the tops but as it is not available, pure aluminum (99.99%) is used, presenting engineering problems. This aluminum is produced at the Elektrochemisches Kombinat in Bitterfeld\* in bars, shipped to Hettstedt for rolling and furnished to the Fischer plant for use. The purity of the aluminum has reportedly been checked at Hettstedt. Because this aluminum has only 1/3 the elasticity and tensile strength of 99.5 aluminum, the sheets have to be rolled to a thickness of 10mm. Each square meter of this 10mm-thick aluminum weighs 27 kg, and the maximum size for each sheet is 3 m<sup>2</sup>. The tops of the reactors (50 m<sup>3</sup>) are two and one-half meters in diameter and three meters high.
4. The monthly production of this very pure aluminum at the Elektrochemisches Kombinat is now fifteen tons, of which ten go to the Fischer plant and five to the USSR. It had originally been planned that the Fischer plant would receive only five tons and the USSR, ten, but this quantity was not sufficient to meet the plant's requirements. When the plant management requested ten tons of this aluminum per month, the Elektrochemisches Kombinat refused, and the matter was taken to the Soviet Administration in Karlshorst. The latter also objected to the increase, but Krasnovitsky (phonetic spelling), of the main SAG office in Berlin-Weissenhof, obtained the approval of Moscow for the additional allocation.

25X1A

CLASSIFICATION SECRET

STATE	<input checked="" type="checkbox"/>	NAVY	<input checked="" type="checkbox"/>	USRB	<input checked="" type="checkbox"/>	DISTRIBUTION													
ARMY	<input checked="" type="checkbox"/>	AIR	<input checked="" type="checkbox"/>	FBI	<input checked="" type="checkbox"/>														

CONFIDENTIAL

This document is hereby regraded to CONFIDENTIAL in accordance with the letter of 16 October 1978 from the Director of Central Intelligence to the Archivist of the United States.

Document No.

No Change in Class

☒ Reclassified

Class Changed To: TS S C

Auth: HR 702

By: